

Engineering Conferences International ECI Digital Archives

Electric Field Assisted Sintering and Related
Phenomena Far From Equilibrium

Proceedings

Winter 3-10-2016

Processing high strength low oxide and metal impurity ZrB₂ ceramics using boron carbide and spark plasma sintering

Erica Corral
University of Arizona

Follow this and additional works at: http://dc.engconfintl.org/efa_sintering



Part of the [Engineering Commons](http://dc.engconfintl.org/efa_sintering)

Recommended Citation

Erica Corral, "Processing high strength low oxide and metal impurity ZrB₂ ceramics using boron carbide and spark plasma sintering" in "Electric Field Assisted Sintering and Related Phenomena Far From Equilibrium", Rishi Raj (University of Colorado at Boulder, USA) Thomas Tsakalakos (Rutgers University, USA) Eds, ECI Symposium Series, (2016). http://dc.engconfintl.org/efa_sintering/42

This Abstract is brought to you for free and open access by the Proceedings at ECI Digital Archives. It has been accepted for inclusion in Electric Field Assisted Sintering and Related Phenomena Far From Equilibrium by an authorized administrator of ECI Digital Archives. For more information, please contact franco@bepress.com.

Processing High Strength Low Oxide and Metal Impurity ZrB₂ Ceramics Using Boron Carbide and Spark Plasma Sintering

David Pham and Erica L. Corral

Materials Science and Engineering Department, The University of Arizona, Tucson, Arizona 85748, United States

Abstract

Zirconium diboride is an ultra-high temperature ceramic (UHTC) with attractive material properties for use in extreme hypersonic flight environments and energy applications. The diboride phase is the basis for high temperature oxidation resistant UHTC composites using secondary phase reinforcements that also enhance high temperature properties of ZrB₂-based composites. However, the mechanical properties are limited by the impurity content found in the diboride source powder. Thus our work focuses on developing a methodology to process the high purity ZrB₂ using spark plasma sintering (SPS) and computational thermodynamics analysis coupled with high-resolution atomic scale electron microscopy. A clear path towards processing ultra-high purity ZrB₂ ceramics is presented using a combined experimental and thermodynamically assisted processing method through thermal treatments and oxide reducing agents carbon and boron carbide (B₄C). Computational thermodynamic phase diagrams consisting of the Zr-O-C ternary and Zr-B-C-O quaternary are developed to predict and explain the microstructures found after SPS. Scanning electron microscopy (SEM) and scanning transmission electron microscopy (STEM) analysis shows evidence of SPS-unique grain boundary cleaning and the potential to use current to further improve ZrB₂+B₄C purity. The effect of current density and computational simulations of predicted temperature during SPS will also be discussed.